

<- Back

Forward ->

Document ID# 776629
2002 Chevrolet Corvette

Feedback

Print

Wheel Alignment Specifications

RPO	Operation	Service Preferred	Tolerance
Front Alignment Specifications			
All	Front Individual Toe	+ 0.04	+/- 0.10
All	Front Sum Toe	+ 0.08	+/- 0.20
All	Steering Wheel Angle	0.0	+/- 1.0
FE1 & FE3	Front Individual Caster	+ 7.4	+/- 0.5
FE1 & FE3	Front Cross Caster	Within +/- 0.5	--
FE1 & FE3	Front Individual Camber	- 0.20	+/- 0.5
FE1 & FE3	Front Cross Camber	Within +/-0.5	--
FE4 (Z06)	Front Individual Caster	+ 6.9	+/- 0.5
FE4 (Z06)	Front Cross Caster	Within +/- 0.5	--
FE4 (Z06)	Front Individual Camber	- 0.70	+/- 0.5
FE4 (Z06)	Front Cross Camber	Within +/- 0.5	--
Rear Alignment Specifications			
All	Rear Individual Toe	- 0.01	+/- 0.10
All	Rear Sum Toe	- 0.02	+/- 0.20
All	Rear Thrust Angle	0.0	+/- 0.10
FE1 & FE3	Rear Individual Camber	- 0.18	+/- 0.5
FE1 & FE3	Rear Cross Camber	Within +/- 0.5	--
FE4 (Z06)	Rear Individual Camber	- 0.68	+/- 0.5
FE4 (Z06)	Rear Cross Camber	Within +/- 0.5	--

<- Back

Forward ->

Document ID# 776629
2002 Chevrolet Corvette

Feedback

Print